

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
7 February 2002 (07.02.2002)

PCT

(10) International Publication Number
WO 02/09966 A1

- (51) International Patent Classification⁷: **B60K 23/08**, 17/346
- (74) Agents: **JENNINGS, Nigel, Robin et al.**; Kilburn & Strode, 20 Red Lion Street, London WC1R 4PJ (GB).
- (21) International Application Number: PCT/GB01/03203
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (22) International Filing Date: 16 July 2001 (16.07.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0018509.0 27 July 2000 (27.07.2000) GB
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (*for all designated States except US*): **RI-CARDO MTC LIMITED** [GB/GB]; Southam Road, Radford Semele, Leamington Spa, Warwickshire CV31 1FQ (GB).
- Published:
— with international search report
- (72) Inventor; and
(75) Inventor/Applicant (*for US only*): **LIPMAN, John, Michael** [GB/GB]; Elmdown House, 66 Banbury Road, Ettington, Warwickshire CV37 7SU (GB).
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: VEHICLE TRANSMISSION SYSTEMS



WO 02/09966 A1

(57) Abstract: A transmission system for a four wheel drive vehicle includes an input shaft (2) connected to a differential mechanism (4, 6, 10), which has two output shafts (12, 20), which are connected, in use, to respective pairs of driven wheels of the vehicle. The two output shafts carry first and second coaxially mounted sun wheels (S1, S2, respectively), of an epicyclic gear system which mesh with first and second sets of planet wheels (P1, P2, respectively), the epicyclic gear system including a third sun wheel (S3), which is mounted coaxially with the first and second sun wheels and is in mesh with a third set of planet wheels (P3). The gear ratios of the three meshing sun wheels and sets of planet wheels are different. Each first planet wheel (P1) is connected to respective second and third planet wheels (P2, P3) to rotate therewith about a respective common planet shaft, the planet shafts being connected to a common carrier (24) which is rotatably mounted coaxially with the three sun wheels. The carrier is connected to one side of a first clutch (28), the other side of which is connected to a fixed structure. The third sun wheel is connected to one side of a second clutch (34), the other side of which is connected to a fixed structure. The transmission system also includes at least one sensor (38) arranged to produce a signal indicative of an operating parameters of the vehicle or its engine and a controller (36) connected to the sensor and to the two clutches and arranged to operate the clutches in response to the said signal.

VEHICLE TRANSMISSION SYSTEMS

The present invention relates to vehicle transmission systems and is concerned with transmission systems for four wheel drive vehicles.

5

Automotive differentials are of course well known and include a single input shaft, normally connected to the output shaft of the vehicle gearbox, and two output shafts which are permitted to rotate at different speeds. The mean of these two speeds is directly proportional to the input speed. When a vehicle
10 travels on a radius, that is to say goes round a corner, the outer wheels travel further than the inside wheels in the same time and must therefore rotate faster. The basic differential caters for this speed difference but the torque supplied to both wheels remains the same. However, there are many circumstances in which it is desirable for the torque supplied to the two wheels to differ. Thus if
15 one wheel is on a low friction surface, e.g. ice, and the other on a high friction surface, e.g. a dry patch of roadway, the maximum torque that can be transmitted to the two wheels by a conventional differential is limited to the very low torque value which may be transmitted to that wheel which is in contact with the ice. The potential propulsive force available through the wheel
20 in engagement with the high friction surface cannot be used and the propulsive force exerted may therefore be insufficient to move the vehicle. A vehicle cornering with a high lateral acceleration has a significant weight transfer from the inside wheels onto the outer wheels. As a result of the reduced weight on the inside wheels, only a low torque can be transmitted through the inside
25 driven wheel before wheel slip occurs and this means that, with a conventional differential, only the same low torque may be transmitted to the outer driven wheel. This severely limits the potential acceleration of the vehicle, when

cornering. In order to overcome these disadvantages, numerous devices are known to lock or limit slip in the differential, whereby different levels of torque may be transmitted through the two output shafts.

5 In the case of a four wheel drive vehicle, there is conventionally a differential between the front and rear axles to accommodate the speed differences between them whilst transmitting power to both axles. In this case also there are many circumstances under which a simple differential is inadequate. A four wheel drive facility is generally provided on vehicles with an excess of power and superior performance could therefore be achieved by transmitting the maximum amount of power through all the wheels. The maximum rate of acceleration can only be achieved if the torque is proportioned between the wheels to match the weight distribution of the vehicle. As a result of dynamic weight transfer, e.g. under heavy acceleration, as much as 80% of the weight may be carried by the rear wheels. An unequal torque distribution could be achieved by providing a differential with an invariable torque split to match this proportion but when cornering or driving on an icy road this torque split ratio could result in vehicle instability and thus loss of control. Under these conditions it would be advantageous for a higher proportion of the torque to be provided to the front axle.

In the case of "off road" vehicles, which frequently have a short wheel base and a high centre of gravity, the weight transfer when climbing a steep gradient could be as much as 90% onto the rear axle. A limited slip type of differential could deliver sufficient traction but could also cause slippage of the front wheels, thereby leading to loss of stability. Locking the centre differential, that is to say the differential between the front and rear axles, would prevent front

wheel slip but reduces manoeuvrability which is a significant problem on the poor surfaces which are commonly encountered when driving off road.

5 When descending a steep gradient, the safest technique is to use a low gear ratio and rely solely or principally on engine braking to maintain control. Under these circumstances, the weight transfer that occurs may place as much as 90% of the vehicle weight onto the front axle.

10 It is therefore the object of the invention to provide a transmission system for four wheel drive vehicles which will split the engine torque between the front and rear axles in a proportion which is variable in dependence on one or more operating parameters of the vehicle or its engine rather than merely limiting the slip of or locking the differential.

15 According to the present invention, there is provided a transmission system for a four wheel drive vehicle including an input shaft connected to a differential mechanism, which has two output shafts, which are connected, in use, to respective pairs of driven wheels of the vehicle, the two output shafts carrying first and second coaxially mounted sun wheels, respectively, of an epicyclic gear system which mesh with first and second sets of planet wheels,
20 respectively, the epicyclic gear system including a third sun wheel, which is mounted coaxially with the first and second sun wheels and is in mesh with a third set of planet wheels, the gear ratios of the first sun wheel with the first set of planet wheels, the second sun wheel with the second set of planet wheels and
25 the third sun wheel with the third set of planet wheels being different, each first planet wheel being connected to respective second and third planet wheels to rotate therewith about a respective common planet shaft, the planet shafts being

connected to a common carrier which is rotatably mounted coaxially with the first, second and third sun wheels, the carrier being connected to a first selectively operable speed changing device, the third sun wheel being connected to a second selectively speed changing device, the transmission system further including at least one sensor arranged to produce a signal indicative of an operating parameter of the vehicle or its engine and a controller connected to the sensor and to the two speed changing device and arranged to operate the speed changing devices in response to the said signal. The present invention also embraces a four wheel drive vehicle incorporating such a transmission system.

Thus a four wheel drive vehicle in accordance with the present invention will typically include not only a front differential splitting speed and/or torque between the two front driven wheels, a rear differential splitting speed and/or torque between the two rear driven wheels and a centre differential splitting speed between the front and rear axles but also an epicyclic gear system, which is connected to the two outputs of the centre differential and includes two speed changing devices which are actuated by a controller in response to a signal received from one or more sensors which detect respective operating parameters of the vehicle or its engine to split the engine torque between the front and rear axles in a proportion which is the optimum for the prevailing operating conditions.

Thus in the transmission system in accordance with the invention there are two speed changing devices which are arranged to change the speed of the carrier and the third sun wheel, respectively, thereby varying the proportion of the engine torque supplied to the front and rear axles of the vehicle. The speed

changing means may be arranged to increase or decrease the speed of the carrier and the third sun wheel. They may therefore constitute e.g. electric motors. It is, however, preferred that the speed changing devices are arranged to reduce the speed of rotation of the carrier and the third sun wheel and may thus constitute simple braking mechanisms. It is, however, preferred that they constitute clutches.

Further features and details of the invention will be apparent from the following description of two specific embodiments of transmission systems in accordance with the invention which is given by way of example only with reference to the two accompanying highly diagrammatic drawings.

Figure 1 shows a transmission system with an input shaft 2 which, in use, will be connected to or constitute part of the output from the gearbox of the vehicle engine. The shaft 2 is connected to the annulus 4 of an epicyclic differential. Formed on the interior of the annulus 4 is an annular array of gear teeth with which the teeth on a number of planet gears 6 mesh. The planet gears 6 are carried by a common carrier 8 and mesh with a sun gear 10. The carrier 8 is connected to a first hollow output shaft 12 which is connected to the front axle of the vehicle, not shown, by way of a gear train 14,16,18. The sun gear 10 is carried by a shaft 20 which is connected to the rear axle, typically through the rear differential.

The output shafts 12 and 20 are connected to a further epicyclic differential gear system which splits the torque transmitted through the two output shafts in a manner appropriate to the operating conditions of the vehicle. The front wheel output shaft 12 carries a sun gear S1 and the rear wheel output shaft 20 carries a

- coaxial sun gear S2. Mounted concentrically with these two sun gears is a further sun gear S3. The three sun wheels S1,S2 and S3 are in mesh with respective sets of three planet wheels P1, P2 and P3. The various planet wheels are associated with one another in three groups, each group including a first planet wheel P1, a second planet wheel P2 and a third planet wheel P3, connected together to form a composite unit. Each composite planet unit P1, P2, P3 is mounted to rotate about a respective planet shaft 22. The three planet shafts 22, which extend parallel to the output shafts 12 and 20, are connected to a common carrier 24. Projecting radially from the carrier 24 are one or more radial clutches 26 which constitute one half of a first selectively actuatable clutch 28, referred to as the rear bias clutch, the other half of which constitutes or is connected to a fixed structure 30, e.g. the outer casing of the epicyclic torque splitting differential system.
- 15 The sun gear S3 is also connected to one or more radial clutch discs 32 which constitute one half of a second selectively operable clutch 34, referred to as the front bias clutch, the other half of which is also connected to or constituted by the fixed structure 30.
- 20 The two clutches 28,34 are connected to a power source (not shown) and may be operated independently under the control of an electronic controller 36. Connected to the controller is a plurality of sensors, of which only one, 38, is shown schematically arranged to sense, and produce a signal representative of, a number of operating parameters of the vehicle and/or its engine, such as the vehicle speed, the steering wheel angle, the acceleration of the vehicle in each of three orthogonal directions, engine speed, engine torque, yaw rate, which

angle, the side forces and the traction characteristics whilst entering, passing through and leaving a corner. The vehicle stability may also be maximised, especially under high speed and adverse weather conditions.

- 5 Although only the front or rear bias clutch would be engaged at any one time, it is also possible to engage both clutches simultaneously and this will effectively lock the centre differential and constitute an anti-theft device for the vehicle or provide a "hill hold" facility. The controller may be arranged to release both the clutches once the input torque exceeds the sum of the wind-up torque
- 10 holding the front and rear axles. Immediately after release of the clutches, the controller may be arranged to apply the rear bias clutch to direct torque preferentially to the rear axle, if appropriate. This facility is, however, not required when the vehicle is facing downhill, unless reverse gear is selected.
- 15 Due to the fact that a significant proportion of the weight of a vehicle is shifted forwardly onto the front axle during braking, the front wheel brakes of a vehicle need to have a performance capability of e.g. two to three times that of the rear wheel brakes. However, it will be appreciated that the ability of the transmission system in accordance with the present invention to transfer torque
- 20 between the front and rear axles under drive conditions can be used to transfer torque between the two axles under braking conditions also. This facility will enable the rear brakes to be sized to match the front brakes, which is currently not necessary, and thus enable the vehicle to achieve a substantially enhanced braking capability by comparison with known vehicles.

CLAIMS

1. A transmission system for a four wheel drive vehicle including an input
5 shaft connected to a differential mechanism, which has two output shafts, which
are connected, in use, to respective pairs of driven wheels of the vehicle, the
two output shafts carrying first and second coaxially mounted sun wheels,
respectively, of an epicyclic gear system which mesh with first and second sets
of planet wheels, respectively, the epicyclic gear system including a third sun
10 wheel, which is mounted coaxially with the first and second sun wheels and is
in mesh with a third set of planet wheels, the gear ratios of the first sun wheel
with the first set of planet wheels, the second sun wheel with the second set of
planet wheels and the third sun wheel with the third set of planet wheels being
different, each first planet wheel being connected to respective second and third
15 planet wheels to rotate therewith about a respective common planet shaft, the
planet shafts being connected to a common carrier which is rotatably mounted
coaxially with the first, second and third sun wheels, the carrier being connected
to a first selectively operable speed changing device, the third sun wheel being
connected to a second selectively speed changing device, the transmission
20 system further including at least one sensor arranged to produce a signal
indicative of an operating parameter of the vehicle or its engine and a controller
connected to the sensor and to the two speed changing devices and arranged to
operate the speed changing devices in response to the said signal.
- 25 2. A transmission system as claimed in Claim 1 in which the first and
second speed changing devices are arranged to reduce the speed of rotation of
the carrier and the third sun wheel, respectively.

3. A transmission system as claimed in Claim 2 in which the first speed changing device comprises a clutch, one side of which is connected to the carrier and the other side of which is connected to a fixed structure, and the second speed changing device comprises a clutch, one side of which is
5 connected to the third sun wheel and the other side of which is connected to a fixed structure.

4. A transmission system as claimed in Claim 1 in which the differential mechanism comprises an epicyclic gearset including an annulus in mesh with a
10 set of planet wheels, which are carried by a carrier and are also in mesh with a sun wheel, the carrier and the sun wheel being connected to the two output shafts.




FIG. 1




FIG. 2

INTERNATIONAL SEARCH REPORT

Int. Application No
PCT/GB 01/03203A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B60K23/08 B60K17/346

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B60K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 424 054 A (FUJI HEAVY IND LTD) 24 April 1991 (1991-04-24) the whole document	1
A	EP 0 413 436 A (FUJI HEAVY IND LTD) 20 February 1991 (1991-02-20) the whole document	1



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *8* document member of the same patent family

Date of the actual completion of the international search

8 October 2001

Date of mailing of the international search report

15/10/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Topp, S

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No
PCT/GB 01/03203

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 0424054	A	24-04-1991	JP	2528003 B2	28-08-1996
			JP	3135835 A	10-06-1991
			JP	2612766 B2	21-05-1997
			JP	3135836 A	10-06-1991
			JP	2528004 B2	28-08-1996
			JP	3135837 A	10-06-1991
			JP	2528005 B2	28-08-1996
			JP	3135838 A	10-06-1991
			DE	69005976 D1	24-02-1994
			DE	69005976 T2	19-05-1994
			EP	0424054 A2	24-04-1991
			US	5080641 A	14-01-1992
EP 0413436	A	20-02-1991	JP	2922924 B2	26-07-1999
			JP	3054030 A	08-03-1991
			DE	69003206 D1	14-10-1993
			DE	69003206 T2	28-04-1994
			EP	0413436 A1	20-02-1991
			US	5071396 A	10-12-1991

Form PCT/ISA/210 (patent family annex) (July 1992)